

WIND

Combined Wind Transmitter

Part number: 4.3324.32.000

The cup star revolution is scanned opto-electronically in contact-free and wear-resistant manner. It has an extremely low starting speed.

The position of the wind vane is detected opto-electronically by a code disc. The output signals are available as 8-bit gray code on 8 parallel lines.

The heating is controlled electronically. A plug connection is situated in the shaft of the instrument.

The instrument is mounted preferably onto a mast. All main parts are made of anodised aluminium.



Specification

Part number: 4.3324.32.000

Wind speed

Measuring range	0.3 ... 50 m/s
Accuracy	±0.4 m/s or ±2.5 %
Delay distance	< 5 m

Wind direction

Measuring range	0 ... 360 °
Resolution	2.5 °
Accuracy	±1.5 °
Starting value	< 0.6 m/s at 90°
Damping ration	> 0.3 acc. to ASTM D 5096-96

Data output digital

Wind speed	0 ... 1042 Hz
Wind direction	8 bit gray code (parallel)

Operating voltage

Electronic	3.3 ... 28 V DC
Heating	24 V AC/DC, 40 W

General

Ambient temp.	-35 ... +80 °C
Electr. connection	19 pol. plug connection
Mounting	onto mast tube Ø 1,5''
Protection	IP 55



Dimension	Ø 800 x 620 mm
Survival speed	60 m/s
Weight	2.8 kg
Fixing boring	Ø 50 x 50 mm

Versions

No other versions of this product are available.

Accessories

No accessories are available for this product.

