

## WIND

### Combined Wind Transmitter

**Part number: 4.3324.32.xxx**

The cup star revolution is scanned opto-electronically in contact-free and wear-resistant manner. It has an extremely low starting speed.

The position of the wind vane is detected opto-electronically by a code disc. The digital measuring signals are transformed by an internal measuring transformer. The output signals are available as current or voltage signals.

The heating is controlled electronically. A plug connection is situated in the shaft of the instrument. The instrument is mounted preferably onto a mast. All main parts are made of anodised aluminium.



### Specification

**Part number: 4.3324.32.xxx**

Wind speed	
Measuring range	0.3 ... 50 m/s for 4.3324.32.0xx 0.3 ... 60 m/s for 4.3324.32.6xx
Accuracy	±0.4 m/s or ±2.5 %
Delay distance	< 5 m
Wind direction	
Measuring range	0 ... 360 °
Resolution	2.5 °
Accuracy	±1.5 °
Starting value	< 0.6 m/s at 90 °
Damping ration	> 0.3 acc. to ASTM D 5096-96
Data output analog	
Wind speed	see models
Wind direction	see models
Operating voltage	
Electronic	see models
Heating	24 V AC/DC, 40 W
General	
Ambient temp.	-35 ... +80 °C
Electr. connection	7 pol. plug connection
Mounting	onto mast tube Ø 1,5"



Protection	IP 55
Dimension	Ø 800 x 620 mm
Survival speed	60 m/s
Weight	2.8 kg
Fixing boring	Ø 50 x 50 mm

## Versions

As per 4.3324.32.xxx, but:

### Product number 4.3324.32.040

<b>Wind speed</b>	
Measuring range	0.3 ... 50 m/s
<b>Data output analog</b>	
Wind speed	0 ... 20 mA
Wind direction	0 mA ... 20 mA
<b>Operating voltage</b>	
Electronic	12 ... 28 V DC

### Product number 4.3324.32.041

<b>Wind speed</b>	
Measuring range	0.3 ... 50 m/s
<b>Data output analog</b>	
Wind speed	4 ... 20 mA
Wind direction	4 ... 20 mA
<b>Operating voltage</b>	
Electronic	12 ... 28 V DC

### Product number 4.3324.32.061

<b>Wind speed</b>	
Measuring range	0.3 ... 50 m/s
<b>Data output analog</b>	
Wind speed	0 ... 10 V
Wind direction	0 ... 10 V
<b>Operating voltage</b>	
Electronic	12 ... 28 V DC

### Product number 4.3324.32.073

<b>Wind speed</b>	
Measuring range	0.3 ... 50 m/s
<b>Data output analog</b>	
Wind speed	0 ... 5 V
Wind direction	0 ... 5 V
<b>Operating voltage</b>	



Electronic	8 ... 28 V DC
------------	---------------

**Product number 4.3324.32.640**

**Wind speed**

Measuring range	0.3 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 20 mA
------------	-------------

Wind direction	0 ... 20 mA
----------------	-------------

**Operating voltage**

Electronic	12 ... 28 V DC
------------	----------------

**Product number 4.3324.32.641**

**Wind speed**

Measuring range	0.3 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	4 ... 20 mA
------------	-------------

Wind direction	4 ... 20 mA
----------------	-------------

**Operating voltage**

Electronic	12 ... 28 V DC
------------	----------------

**Product number 4.3324.32.661**

**Wind speed**

Measuring range	0.3 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 10 V
------------	------------

Wind direction	0 ... 10 V
----------------	------------

**Operating voltage**

Electronic	12 ... 28 V DC
------------	----------------

**Product number 4.3324.32.673**

**Wind speed**

Measuring range	0.3 ... 60 m/s
-----------------	----------------

**Data output analog**

Wind speed	0 ... 5 V
------------	-----------

Wind direction	0 ... 5 V
----------------	-----------

**Operating voltage**

Electronic	8 ... 28 V DC
------------	---------------

## Accessories

No accessories are available for this product.

