

RADIATION

Pyranometer GSM 10.7

Part number: 7.1415.05.xxx

The measurement is cos-corrected. Delivery includes calibration certificate.



Specification

Part number: 7.1415.05.xxx

Radiation	
Measuring range	0 ... 1300 W/m ²
Cosinus-correction	error f2 < 3 %
Spectral range	380 ... 2800 nm
Non-linearity	<5 %
Abs. error	< ±10 %
Diffuser	PTFE
Dome	optical glas
Sensor type	thermocouples
General	
Ambient temp.	-20 ... +60 °C
Electr. connection	plug with 5 m cable
Dimension	Ø 80 x 86 mm
Weight	0.3 kg

Versions

As per 7.1415.05.xxx, but:

Product number 7.1415.05.041

Data output analog



Output type	4 ... 20 mA
-------------	-------------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.240

Data output digital

Protocol	ASCII
----------	-------

Output type	2 wire RS485
-------------	--------------

Data output analog

Output type	0 ... 20 mA
-------------	-------------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.241

Data output digital

Protocol	ASCII
----------	-------

Output type	2 wire RS485
-------------	--------------

Data output analog

Output type	4 ... 20 mA
-------------	-------------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.251

Data output digital

Protocol	ASCII
----------	-------

Output type	2 wire RS485
-------------	--------------

Data output analog

Output type	0 ... 5 V
-------------	-----------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.261

Data output digital

Protocol	ASCII
----------	-------

Output type	2 wire RS485
-------------	--------------

Data output analog

Output type	0 ... 10 V
-------------	------------

General

Power supply	12 ... 28 V DC
--------------	----------------

Product number 7.1415.05.340

Data output digital

Protocol	MODBUS RTU
----------	------------

Output type	2 wire RS485
-------------	--------------

Data output analog

Output type	0 ... 20 mA
-------------	-------------



General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.341
Data output digital

Protocol	MODBUS RTU
Output type	2 wire RS485

Data output analog

Output type	4 ... 20 mA
-------------	-------------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.351
Data output digital

Protocol	MODBUS RTU
Output type	2 wire RS485

Data output analog

Output type	0 ... 5 V
-------------	-----------

General

Power supply	9 ... 28 V DC
--------------	---------------

Product number 7.1415.05.361
Data output digital

Protocol	MODBUS RTU
Output type	2 wire RS485


Data output analog

Output type	0 ... 10 V
-------------	------------




General

Power supply	12 ... 28 V DC
--------------	----------------

Accessories

Product	Product name	Brief description
	Traverse 0,8 m 4.3171.40.002	For mounting of a Pyranometer CMP11 / 6 / 3 And a sunshine duration sensor-CSD3 onto a mast.
		General
		Clamping range
		Ø 48 ... 102 mm
		Sensor distance
		0.4 / 0.8 m from mast
		Material
		Aluminium / Stainless steel
		Weight
		1 kg



	<p>Hanger 1 m (for radiation sensors) 4.3185.xx.009</p>	<p>The hanger is used for laterally mounting of a radiation- or brightness transmitter onto a mast.</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Length</td> <td>1 m</td> </tr> <tr> <td>Material</td> <td>Aluminium</td> </tr> <tr> <td>Tube diameter</td> <td>Ø 50 mm</td> </tr> <tr> <td>Weight</td> <td>1.8 kg</td> </tr> </table>	General		Length	1 m	Material	Aluminium	Tube diameter	Ø 50 mm	Weight	1.8 kg
General												
Length	1 m											
Material	Aluminium											
Tube diameter	Ø 50 mm											
Weight	1.8 kg											
	<p>Adapter Compact 506345</p>	<p>The adapter serves for mounting a radiation transmitter, baro transmitter or brightness transmitter onto a traverse (4.3171.30.000, 4.3171.40.000) or holder (506 347).</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Material</td> <td>Aluminium, anodized</td> </tr> <tr> <td>Dimension</td> <td>100 x 115 x 65 mm</td> </tr> <tr> <td>Weight</td> <td>0.5 kg</td> </tr> </table>	General		Material	Aluminium, anodized	Dimension	100 x 115 x 65 mm	Weight	0.5 kg		
General												
Material	Aluminium, anodized											
Dimension	100 x 115 x 65 mm											
Weight	0.5 kg											
	<p>Adapter Compact 0 ... 90 ° adjustable 508850</p>	<p>The adapter serves for mounting a radiation transmitter, baro transmitter or brightness transmitter onto a traverse (4.3171.30.000, 4.3171.40.000) or holder (506 347).</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Material</td> <td>Aluminium, anodized</td> </tr> <tr> <td>Dimension</td> <td>100 x 115 x 65 mm</td> </tr> <tr> <td>Weight</td> <td>0.5 kg</td> </tr> <tr> <td>Function</td> <td>0 ... 90 ° adjustable</td> </tr> </table>	General		Material	Aluminium, anodized	Dimension	100 x 115 x 65 mm	Weight	0.5 kg	Function	0 ... 90 ° adjustable
General												
Material	Aluminium, anodized											
Dimension	100 x 115 x 65 mm											
Weight	0.5 kg											
Function	0 ... 90 ° adjustable											

