

WIND

Wind Direction Transmitter Compact

Part number: 4.3129.80.xxx

Measuring transmitter for the measurement of the horizontal wind direction with serial output signal. The wind vane consists of fibre-glass reinforced, the housing is made of anodised aluminium and plastic.

The instrument has a threaded pin PG 21 with 2 nuts for mounting.

For the more difficult use in the high mountains or at other critical sites, where icing might be expected frequently, the wind transmitters can be equipped with a reinforced heating.

Please contact us for the required model, order-no., and availability.



Specification

Part number: 4.3129.80.xxx

Wind direction

Measuring range	0 ... 360 °
Resolution	0.4 °
Accuracy	±2 °

Operating voltage

Electronic	8 ... 30 V DC or 24 V AC
Heating	24 V AC/DC, max 60 W

General

Ambient temp.	-30 ... +70 °C
Electr. connection	12 m cable LiYCY 6 x 0.5 mm ²
Protection	IP 55

Versions

As per 4.3129.80.xxx, but:

Product number 4.3129.80.141

Data output analog

Stromausgang	max. 500
Wind direction	4 ... 20 mA

Operating voltage



Electronic	> 12 V DC or 24 V AC
------------	----------------------

General

Electr. connection	12 m cable LiYCY 6 x 0.25 mm ²
Dimension	Ø 330 x 220 mm
Weight	1.1 kg

Product number 4.3129.80.741

Data output analog

Stromausgang	max. 500
Wind direction	4 ... 20 mA

Operating voltage

Electronic	> 12 V DC or 24 V AC
------------	----------------------

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.80.761

Data output analog

Wind direction	0 ... 10 V
Voltage output	min. 1000

Operating voltage

Electronic	> 12 V DC or 24 V AC
------------	----------------------

General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Product number 4.3129.80.773


Data output analog

Wind direction	0 ... 5 V
Voltage output	min. 1000




General

Electr. connection	7 pol. plug
Dimension	Ø 330 x 270 mm
Weight	0.4 kg

Accessories

Product	Product name	Brief description
	Traverse compact for wall mounting 4.3171.2x.000	For storefront mounting of a measuring value transmitter. General Material Aluminium



	<p>Traverse for Wind Transmitters Compact 4.3171.3x.000</p>	<p>For mounting the wind transmitter and wind direction transmitter jointly onto a mast.</p> <table border="1"> <tr> <td colspan="2">Material</td> </tr> <tr> <td>Traverse</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Gripping clamb</td> <td>stainless steel</td> </tr> <tr> <td colspan="2">General</td> </tr> <tr> <td>Sensor distance horizontal</td> <td>0.8 m</td> </tr> <tr> <td>Weight</td> <td>0.35 kg</td> </tr> <tr> <td>Fixing boring</td> <td>hole Ø 29 mm</td> </tr> </table>	Material		Traverse	aluminium (AlMgSi0.5)	Gripping clamb	stainless steel	General		Sensor distance horizontal	0.8 m	Weight	0.35 kg	Fixing boring	hole Ø 29 mm
Material																
Traverse	aluminium (AlMgSi0.5)															
Gripping clamb	stainless steel															
General																
Sensor distance horizontal	0.8 m															
Weight	0.35 kg															
Fixing boring	hole Ø 29 mm															
	<p>Traverse short for Wind Transmitters Compact 4.3171.4x.000</p>	<p>For mounting one wind transmitter or wind direction transmitter at a mast.</p> <table border="1"> <tr> <td colspan="2">Material</td> </tr> <tr> <td>Traverse</td> <td>aluminium (AlMgSi0.5)</td> </tr> <tr> <td>Gripping clamb</td> <td>stainless steel</td> </tr> <tr> <td colspan="2">General</td> </tr> <tr> <td>Sensor distance horizontal</td> <td>0.4 m</td> </tr> <tr> <td>Weight</td> <td>0.3 kg</td> </tr> <tr> <td>Fixing boring</td> <td>hole Ø 29 mm</td> </tr> </table>	Material		Traverse	aluminium (AlMgSi0.5)	Gripping clamb	stainless steel	General		Sensor distance horizontal	0.4 m	Weight	0.3 kg	Fixing boring	hole Ø 29 mm
Material																
Traverse	aluminium (AlMgSi0.5)															
Gripping clamb	stainless steel															
General																
Sensor distance horizontal	0.4 m															
Weight	0.3 kg															
Fixing boring	hole Ø 29 mm															
	<p>Holder compact 506347</p>	<p>The holder serves for the mounting of a wind transmitter, Compact-type, onto an instrument carrier or mast.</p> <table border="1"> <tr> <td colspan="2">General</td> </tr> <tr> <td>Mounting</td> <td>for mast tubes Ø 35 ... 50 mm</td> </tr> <tr> <td>Material</td> <td>stainless steel (V2A)</td> </tr> <tr> <td>Dimension</td> <td>80 x 150 mm</td> </tr> <tr> <td>Weight</td> <td>0.35 kg</td> </tr> <tr> <td>Fixing boring</td> <td>hole Ø 32.5 mm</td> </tr> </table>	General		Mounting	for mast tubes Ø 35 ... 50 mm	Material	stainless steel (V2A)	Dimension	80 x 150 mm	Weight	0.35 kg	Fixing boring	hole Ø 32.5 mm		
General																
Mounting	for mast tubes Ø 35 ... 50 mm															
Material	stainless steel (V2A)															
Dimension	80 x 150 mm															
Weight	0.35 kg															
Fixing boring	hole Ø 32.5 mm															

